


## Technical Data

Measures	Units/m <sup>2</sup>	Weight/m <sup>2</sup>	Material	Finishes	Colours	Decor	
<b>1.</b> 9.5 in x 6.7 in x 1.2 in <b>1.</b> 24 cm x 17 cm x 3 cm	1.37 Units	35 Kg	Concrete (cement and sands 99% and color coating 1%)	Cement Full color Metallic Chamaleon Oxide Leather Marble Decor	CE1-CE15 CB1-CB48 ME1-ME7 CH1-CH3 O1-O5 All CB,CE/ME/O All CB/ME All CB/ME/CE/O	Lienzo Planet Chevron Wood Tye Trend Parasol	Lineas Fosil Trasversal Mariscal Rayas Lineas

1.
















## Packaging

m <sup>2</sup> Box	Weight Box	Pieces Box	Box Palet
0.38 m <sup>2</sup>	13.5 kg	14 Pieces	56 Boxes

## General Material Performance Data

UNE-EN 15286:2013 Agglomerated stone - Slabs and tiles for wall finishes (internal and external)

 <b>REACTION TO FIRE</b> A1	 <b>ABSORPTION</b> W1	 <b>SIZE ACCURACY</b> +/- 0,5%	 <b>THERMAL CONDUCTIVITY</b> 1,3 W/m <sup>2</sup> k	 <b>COLOR TONE DIFFERENCE</b> V1
 <b>FREEZE/THAW RESISTANCE</b> Resistant 97%	 <b>COLOR FASTNESS</b> Unchanging	 <b>ADHESION</b> Appropriate	 <b>SURFACE QUALITY</b> A1	 <b>THERMAL SHOCK RESISTANCE</b> Resistant 92%
 <b>THICKNESS</b> +/- 10%	 <b>IMPACT RESISTANCE</b> 5J	 <b>FLEXURAL STRENGTH</b> F1		

