


## Technical Data

Measures	Units/m <sup>2</sup>	Weight/m <sup>2</sup>	Material	Finishes	Colours	Decor	
<b>1. 5.1 in x 6.3 in x 1 in</b> <b>1. 13 cm x 16 cm</b> x 2.5 cm	1.64 Units	36.2 Kg	Concrete (cement and sands 99% and color coating 1%)	Cement Full color Metallic Chamaleon Oxide Leather Marble Decor	CE1-CE15 CB1-CB48 ME1-ME7 CH1-CH3 O1-O5 All CB,CE/ME/O All CB/ME All CB/ME/CE/O	Lienzo Planet Chevron Wood Tye Trend Parasol	Lineas Fossil Trasversal Mariscal Rayas Lineas

1.
















## Packaging

m <sup>2</sup> Box	Weight Box	Pieces Box	Box Palet
0.23 m <sup>2</sup>	9.9 kg	15 Pieces	80 Boxes

## General Material Performance Data

UNE-EN 15286:2013 Agglomerated stone - Slabs and tiles for wall finishes (internal and external)

 <b>REACTION TO FIRE</b> A1	 <b>ABSORPTION</b> W1	 <b>SIZE ACCURACY</b> +/- 0,5%	 <b>THERMAL CONDUCTIVITY</b> 1,3 W/m <sup>2</sup> k	 <b>COLOR TONE DIFFERENCE</b> V1
 <b>FREEZE/THAW RESISTANCE</b> Resistant 97%	 <b>COLOR FASTNESS</b> Unchanging	 <b>ADHESION</b> Appropriate	 <b>SURFACE QUALITY</b> A1	 <b>THERMAL SHOCK RESISTANCE</b> Resistant 92%
 <b>THICKNESS</b> +/- 10%	 <b>IMPACT RESISTANCE</b> 5J	 <b>FLEXURAL STRENGTH</b> F1		

